

WHI

Elevatore idraulico duplex profilo a doppia H
 Duplex fork lift with double profile "H"
 Élévateur hydraulique duplex avec double profile "H"
 Hydraulischer Duplex-Gabelstapler, Doppelprofilrahmen mit H-Form



Montante duplex doppia "H"
 Duplex "H" profile
 Poteau duplex double "H"
 Doppelter "H" -Duplexpfosten

DATI TECNICI - TECHNICAL DETAILS
 DÉTAILS TECHNIQUES - TECHNISCHE DATEN

3

Levers

Distributor

1 x

Oil - Pressure

25 lt/min 180 bar max

ACCESSORI OPZIONALI - OPTIONAL ACCESSORIES - ACCESSOIRES OPTIONNELS - OPTIONALES ZUBEHÖR **Pag. 206**

DATI TECNICI - TECHNICAL DETAILS - DÉTAILS TECHNIQUES - TECHNISCHE DATEN

| MOD. | COD | nr. | | | | | | |
|--|----------|-----|-------|--------|----------|---------|--------|-----|
| WHI 22-25 | 10692225 | 1 | 2.200 | 250 cm | 75+75 mm | 10°+20° | 205 cm | 325 |
| WHI 22-32 | 10692232 | 1 | 2.200 | 320 cm | 75+75 mm | 10°+20° | 240 cm | 345 |
| WHI 22-36 | 10692236 | 1 | 2.200 | 360 cm | 75+75 mm | 10°+20° | 265 cm | 360 |
| WHI 22-42 | 10692242 | 1 | 2.200 | 420 cm | 75+75 mm | 10°+20° | 300 cm | 420 |
| WHI/GV Grande Visibilità / Great visibility / Grande visibilité / Gute sichtbarkeit | | | | | | | | |
| WHI/GV 22-25 | 10702225 | 2 | 2.200 | 250 cm | 75+75 mm | 10°+20° | 211 cm | 570 |
| WHI/GV 22-32 | 10702232 | 2 | 2.200 | 320 cm | 75+75 mm | 10°+20° | 245 cm | 600 |
| WHI/GV 22-36 | 10702236 | 2 | 2.200 | 360 cm | 75+75 mm | 10°+20° | 271 cm | 700 |
| WHI/GV 22-42 | 10702242 | 2 | 2.200 | 420 cm | 75+75 mm | 10°+20° | 305 cm | 750 |

| OPTIONAL | Descrizione - Description - Description - Beschreibung |
|----------------|---|
| 1M60040 | Maggiorazione attacco al trattore cat. 1-2 per montaggio frontale - Extra price for cat. 1-2 tractor front attachment Supplément pour la fixation au tracteur cat. 1-2 pour montage frontal - Aufpreis für die Befestigung an der Traktorkatze. 1-2 für die Frontmontage |
| 1M60041 | Maggiorazione tubi idraulici al metro - Extra charge for hydraulic pipes per meter Supplément pour les tuyaux hydrauliques par mètre - Aufpreis für Hydraulikleitungen pro Meter |